



# SAFETY DATA SHEET

## SECTION 1 — CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Product Identifier Perlite (All grades including 6510, 6410, 5565, 5100, 5045, 610)		[WHMIS Classification] Not Applicable	
Product Use Light weight aggregate, Horticultural aggregate, Refractory, Insulation, Absorbent.			
Manufacturer's Name Therm-O-Rock East, Inc.		Supplier's Name	
Street Address 1 Pine Street		Street Address	
City New Eagle	State PA	City	State
Postal Code 15067	Emergency Telephone 724-258-3670	Postal Code	Emergency Telephone
Date SDS Prepared 6-18-2020	SDS Prepared By Stanley R. Slawek	Phone Number	(724) 258-3670

## SECTION 2 — HAZARDS IDENTIFICATION

GHS Classification	Eye Irritation -Category 2A, Specific Target Organ Toxicity – Single Exposure-Category 3, Respiratory system.	GHS Symbol 
Signal Word	Warning	
Hazard Statement	Causes skin irritation. May cause respiratory irritation.	
Precautionary Statements	Wear eye protection. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue Rinsing. If eye irritation persists: Get medical attention. Avoid breathing dust. Use only outdoors or in a well ventilated area. IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.	

## SECTION 3 — COMPOSITION/INFORMATION ON INGREDIENTS

Hazardous Ingredients (specific)	%	CAS Number	LD <sub>50</sub> of Ingredient (specify species and route)	LC <sub>50</sub> of Ingredient (specify species)	OSHA PEL (mg/m3)	ACGIH TLV (mg/m3)
Perlite	100	93763-70-3	Not Available	Not Available	10	15
Silica-crystalline quartz	0-1	14808-60-7	22,500 mg/kg	Not Available	30	.025

## SECTION 4 — FIRST AID MEASURES

Skin Contact Use moisture renewing lotions if dryness occurs.
Eye Contact Flush eyes with generous quantities of water or eye rinse solution. Consult physician if irritation persists.
Inhalation Remove to fresh air. Blow nose to evacuate dust.
Ingestion Drink generous amounts of water to reduce bulk and drying effects.

## SECTION 5 — FIRE FIGHTING MEASURES

Flammable	<input type="checkbox"/> Yes <input checked="" type="checkbox"/> No	If yes, under which conditions?
Means of Extinction		
N/A		
Flashpoint (°C) and Method	Upper Flammable Limit (% by volume)	Lower Flammable Limit (% by volume)
None	None	None
Auto ignition Temperature (°C)	Explosion Data — Sensitivity to Impact	Explosion Data — Sensitivity to Static Discharge
Not Combustible	N/A	N/A
Hazardous Combustion Products		
N/A		
NFPA		
N/A		

## SECTION 6 — ACCIDENTAL RELEASE MEASURES

Personal Precautions: If dust is present, use respirator fitted with particulate filter as specified in Section 8. Protect eyes with goggles.
Containment and Cleanup: Vacuum clean dust with equipment fitted with HEPA filter. Use dust suppressant such as water if sweeping is necessary.
Environment: Not considered as hazardous waste by RCRA (40 CFR Part 261). Place waste and spillage in closed containers. Dispose of in approved landfill.

## SECTION 7 — HANDLING AND STORAGE

Handling Procedures and Equipment
Minimize dust generation. Avoid contact with eyes. Avoid breathing dust. Repair or dispose of broken bags.
Storage Requirements
Store in a dry place to maintain packaging integrity and product quality. Do not store near hydrofluoric acid. Observe all label precautions and warnings.

## SECTION 8 — EXPOSURE CONTROL / PERSONAL PROTECTION

Exposure Limits	<input checked="" type="checkbox"/> ACGIH TLV	<input checked="" type="checkbox"/> OSHA PEL	<input type="checkbox"/> Other (specify)
Specific Engineering Controls (such as ventilation, enclosed process)			
Adequate ventilation and appropriate local exhaust where needed to keep dust level below PEL.			
Personal Protective Equipment	<input checked="" type="checkbox"/> Gloves	<input checked="" type="checkbox"/> Respirator	<input checked="" type="checkbox"/> Eye
Footwear	<input type="checkbox"/>	<input type="checkbox"/> Clothing	<input type="checkbox"/> Other
If checked, please specify type			
Eye: Goggles to protect from dust.			
Skin: No special equipment is required.			
Respiratory: Respirators fitted with filters certified to standard 42CFR84 under series N95 should be worn when dust is present. If the dust concentration is less than ten (10) times the Permissible Exposure Limit (PEL) use a quarter or half mask respirator. If dust concentration is greater than ten (10) times and less than fifty (50) times the PEL, a full-face piece respirator fitted with replaceable N95 filters is recommended. If dust concentration is greater than fifty (50) and less than two-hundred (200) times the PEL use a power air-purify (positive pressure) respirator with replaceable N95 filter. If dust concentration is greater than two-hundred (200) times the PEL use a type C, supplied air respirator (continuous flow, positive pressure), with full face piece, hood or helmet.			

## SECTION 9 — PHYSICAL AND CHEMICAL PROPERTIES

Physical State Solid	Odor and Appearance White granules or powder. No distinct odor.	Odor Threshold (ppm) N/A
Specific Gravity 2.35	Vapor Density (air = 1) N/A	Vapor Pressure (mmHg) N/A
Evaporation Rate N/A	Boiling Point (° C) N/A	Freezing Point (° C) N/A
pH 6-10	Coefficient of Water/Oil Distribution N/A	[Solubility in Water] Slightly Soluble

## SECTION 10 — STABILITY AND REACTIVITY

Chemical Stability <input checked="" type="checkbox"/> Yes <input type="checkbox"/> No	If no, under which conditions?
Incompatibility with Other Substances <input checked="" type="checkbox"/> Yes <input type="checkbox"/> No	If yes, which ones? Reacts with Hydrofluoric Acid to form Silicon Tetrafluoride gas
Reactivity and under what conditions?	
No dangerous reactions known.	
Hazardous Decomposition Products	
None	

## SECTION 11 — TOXICOLOGICAL INFORMATION

Effects of Acute Exposure Potential irritant for skin contact, eye contact or inhalation.
Effects of chronic exposure Perlite is a naturally occurring volcanic glass consisting of fused sodium-potassium-aluminum silicate. Tests conducted on Perlite have not identified crystalline silica as being present above the detection limit (0.05%). Although there are not published reports of adverse health effects from exposure to perlite dust, dust levels should be maintained below the OSHA Permissible Exposure Limit for perlite and respirators used when airborne dust is present.
Irritancy of Product Potential irritant for skin contact, eye contact or inhalation.
Skin sensitization Possible through skin contact.
Carcinogenicity-IARC N/A
Reproductive toxicity N/A
Embriotoxicity N/A
Name of synergistic products/effects N/A

## SECTION 12 — ECOLOGICAL INFORMATION

Aquatic Toxicity Generally considered inert. Perlite has no negative ecological effect and may be used as a soil container.
--

## SECTION 13 — DISPOSAL CONSIDERATIONS

Waste Disposal Not considered hazardous waste by the RCRA (40 CFR Part 261). Place waste and spillage in closed containers. Dispose in accordance with Federal, State and Local regulations.
--

## SECTION 14 — TRANSPORT INFORMATION

Special Shipping Information No known shipping regulations.		
TDG N/A	DOT N/A	PIN N/A
IMO N/A	ICAO N/A	

## SECTION 15 — REGULATORY INFORMATION

WHMIS Classification	OSHA Perlite is not considered as a toxic or hazardous subject.
SERA Not Listed	TSCA Not Listed.
Status under CA Proposition 65 This product can expose you to chemicals including Quartz which is known to the state of California to cause cancer. California law requires the above warning in the absence of definitive testing to prove the defined risks do not exist. For more information go to: <a href="http://www.P65warnings.ca.gov">www.P65warnings.ca.gov</a>	
<i>This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the MSDS contains all of the information required by CPR.</i>	

## SECTION 16 — OTHER INFORMATION

Notice: This information relates only to the material designated and may not be valid for such material used in combination with any other materials or in any process. All statements, information and data provided are believed to be accurate and reliable, but are presented without any guarantee, representation, warranty or responsibility of any kind, expressed or implied. Any and all representations and/or warranties of merchantability or fitness for a particular purpose are specifically disclaimed. Users should make their own investigations as to the suitability of the information or product for their particular purpose. Nothing in this document is intended as permission, inducement or recommendation to violate any laws or practice any invention covered by existing patents, copyrights or inventions. Therm-O-Rock East, Inc. does not accept liability for any loss or damage that may occur from the use of this information.